



Controlled Drive Roll Processor Total Control

- ▶ **Streamlined Design**
- ▶ **Rugged and Tough**
- ▶ **True Volume Measurement**
- ▶ **Consistent Delimiting**

		C24B	
Dimensions			
Height	71.5"	182 cm	
Length	97.5"	248 cm	
Width	51.75"	131 cm	
Weight			
Without bracket	6000 lbs	2722 kg	
Cut Capacity (Hultdins Supercut Bar Saw)			
Bottom Cut Capacity	27"	69 cm	
Butt Saw Pitch	0.404 or 3/4"		
Top Cut Capacity	14"	35.5 cm	
Top Saw Pitch	0.404 or 3/4"		
Feeding			
Roll Motors	Variable	Variable	
Roll Opening	28"	71 cm	
Delimiting			
Optimum Delimiting Diameter	24" / 61 cm		
Grab Arm Opening	29" / 74 cm (arm tip to tip)		
Bracket			
Style	Pin On or Quick Attach		
Control and Measuring			
Standard	DASA Management System		
Recommended Specifications of Carrier			
Carrier Class	20 - 25 Ton		
Required Operating Pressure	3550 psi	24.5 MPa	
Required Flow (drive rolls)	80 - 120 gpm	303 - 454 l/m	
Required Flow (arms)	35 gpm	132 l/m	

Ideal for Picking and Placing

Standard Features on all Models:

- ▶ Controlled head
- ▶ Drive roll patterns - various styles to fit application
- ▶ Hultdins Supercut Bar Saw
- ▶ Only 4 lines from processor to carrier (3 hydraulic, 1 electrical)

Options:

- ▶ Fixed displacement roll motors
- ▶ FibreSaver rolls

10820 - 89 AVENUE, GRANDE PRAIRIE, ALBERTA CANADA T8V 6R7
PHONE 780 532-3282 ▼ FAX 780 538-1808



TOLL FREE 1-866-783-7243

e-mail: sales@goRisley.com

www.RisleyEquipment.com

AUTHORIZED DEALER: