



Delimber / Processors The Next Generation

- ▶ **New Feed Roll Arms and Rolls**
- ▶ **Simplified Interface**
- ▶ **Improved Teleboom Cylinder**
- ▶ **New Safety Features**

	Hydraulically Controlled Boom						Cable Controlled Boom			
	LM2000C		LM2600		LM3600		LM2100C		LM2700	
Dimensions										
Height in transport position from center of pivot (bracket and carrier excluded)	27"	69 cm	30"	76 cm	36"	91 cm	27"	69 cm	30"	76 cm
Length (collapsed)	47'	14 m	48'	15 m	48'	15 m	54' / 16 m			
Tube Diameter	26"	66 cm	30"	76 cm	36"	91 cm	26"	66 cm	30"	76 cm

Weight										
With transport layover bracket	22000 lbs	10070 kg	26200 lbs	11884 kg	29300 lbs	13290 kg	24930 lbs	11308 kg	29160 lbs	13227 kg

Topping and Butting										
Circular Topping Saw Max.	18" / 46 cm									
Bar Saw Topping Saw Max. (Hultdins)										
Butting Saw Max. (Hultdins)	34" / 86 cm							34.5"	88 cm	
Butting Saw Chain Pitch					3/4"					

Drive System											
Boom Length	40' / 12 m					50' / 15 m					
Boom Speed	615 ft/min / 187 m/min				461 ft/min	141 m/min	535 ft/min	163 m/min	660 ft/min	200 m/min	
Boom Power	9420 lbf / 4273 kgf				12510 lbf	5674 kgf	6825 lbf / 3096 kgf				

Rolls										
Roll Diameter	26" / 66 cm									
Roll Speed ft/min	1392 ft/min / 424 m/min									
Roll Power	4850 lbf / 21538 N									

Recommended Specifications of Carrier										
Carrier Class	20 ton	22 -25 ton			30 ton	20 - 25 ton		25 ton		
Required Operating Pressure	3000 psi to cylinder, 3500 psi to winch / 21 MPa to cylinder, 24 MPa to winch									
Required Flow	100 gpm / 379 l/m	120 gpm / 454 l/m	140 gpm / 530 l/m		100 gpm / 379 l/m		140 gpm / 530 l/m			

More Efficient and Cost Effective than Ever

Standard Features on all Models:

- ▶ New style transportation bracket and layover geometry
- ▶ New style front delimiting knife
- ▶ New installation kits for easier installs

Options Available:

- ▶ Hultdins Supercut Topping Bar Saw
- ▶ Risley COMS III[®] Measuring
- ▶ Risley FibreSaver[®] Rolls

10820 - 89 AVENUE, GRANDE PRAIRIE, ALBERTA CANADA T8V 6R7
PHONE 780 532-3282 ▼ FAX 780 538-1808



TOLL FREE 1-866-783-7243

e-mail: sales@goRisley.com

www.RisleyEquipment.com

AUTHORIZED DEALER: