



SIDEWINDER

- High Torque Drive Rolls
- Large Wood Processor
- Strong & Reliable
- Full Control





CONTROLLED Drive Roll Processor The BIG WOOD Producer

- ▶ Streamlined Design
- ▶ Effective Delimiting

- ▶ True Volume Measurement
- ▶ 40° Dip Down Control

| | | W26D | |
|---|--|------------------------|---------------|
| Dimensions | | | |
| Height | | 70" | 178 cm |
| Length | | 136" | 345 cm |
| Width | | 66" | 168 cm |
| Weight | | | |
| Without bracket | | 8000 lbs | 3629 kg |
| Cut Capacity (Hultdins Supercut Bar Saw) | | | |
| Bottom Cut Capacity | | 30" | 76 cm |
| Butt Saw Pitch | | 3/4" | |
| Top Cut Capacity | | 14" | 36 cm |
| Top Saw Pitch | | 0.404 | |
| Feeding | | | |
| Roll Motors | | Variable | Variable |
| Roll Opening | | 34" | 81 cm |
| Delimiting | | | |
| Optimum Delimiting Diameter | | 30" / 76 cm | |
| Grab Arm Opening | | 30" / 76 cm | |
| Bracket | | | |
| Style | | Pin On or Quick Attach | |
| Control and Measuring | | | |
| Standard | | DASA Management System | |
| Recommended Specifications of Carrier | | | |
| Carrier Class | | 27 - 30 Ton | |
| Required Operating Pressure | | 3500 - 4500 psi | 24 - 31 MPa |
| Required Flow (drive rolls) | | 80 - 120 gpm | 303 - 454 l/m |
| Required Flow (arms) | | 35 gpm | 132 l/m |

Ideal for Picking and Placing

Standard Features on all Models:

- ▶ Controlled Head
- ▶ Drive Roll patterns - various styles to fit application
- ▶ Only 4 lines from processor to carrier (3 hydraulics, 1 electrical)
- ▶ Hultdins Supercut Bar Saw

10820 - 89 AVENUE, GRANDE PRAIRIE, ALBERTA CANADA T8V 6R7
PHONE 780 532-3282 ▼ FAX 780 538-1808



TOLL FREE 1-866-783-7243

e-mail: sales@goRisley.com
www.RisleyEquipment.com

AUTHORIZED DEALER: