



# CONTROLLED Drive Roll Processor The BIG WOOD Producer

- ▶ Streamlined Design
- ▶ Effective Delimiting

- ▶ True Volume Measurement
- ▶ 40° Dip Down Control

	W26D	
<b>Dimensions</b>		
Height	70"	178 cm
Length	136"	345 cm
Width	66"	168 cm
<b>Weight</b>		
Without bracket	8000 lbs	3629 kg
<b>Cut Capacity (Hultdins Supercut Bar Saw)</b>		
Bottom Cut Capacity	30"	76 cm
Butt Saw Pitch	3/4"	
Top Cut Capacity	14"	36 cm
Top Saw Pitch	0.404	
<b>Feeding</b>		
Roll Motors	Variable	Variable
Roll Opening	34"	81 cm
<b>Delimiting</b>		
Optimum Delimiting Diameter	30" / 76 cm	
Grab Arm Opening	30" / 76 cm	
<b>Bracket</b>		
Style	Pin On or Quick Attach	
<b>Control and Measuring</b>		
Standard	DASA Management System	
<b>Recommended Specifications of Carrier</b>		
Carrier Class	27 - 30 Ton	
Required Operating Pressure	3500 - 4500 psi	24 - 31 MPa
Required Flow (drive rolls)	80 - 120 gpm	303 - 454 l/m
Required Flow (arms)	35 gpm	132 l/m

## Ideal for Picking and Placing

### Standard Features on all Models:

- ▶ Controlled Head
- ▶ Drive Roll patterns - various styles to fit application
- ▶ Only 4 lines from processor to carrier (3 hydraulics, 1 electrical)
- ▶ Hultdins Supercut Bar Saw

10820 - 89 AVENUE, GRANDE PRAIRIE, ALBERTA CANADA T8V 6R7  
PHONE 780 532-3282 ▼ FAX 780 538-1808



**TOLL FREE 1-866-783-7243**

e-mail: [sales@goRisley.com](mailto:sales@goRisley.com)

[www.RisleyEquipment.com](http://www.RisleyEquipment.com)

AUTHORIZED DEALER: